LGS Light pollution investigation in Calar-Alto

F. Delplancke[1], N. Ageorges[2], N. Hubin[1] , C. O'Sullivan[2]

[1] European Southern Observatory
Karl Schwarzschildstrasse 2, D-85748 Garching, Germany
[2] National University of Ireland, Galway
Physics Department, Galway, Ireland

Abstract. Preliminary results of Rayleigh scattering measurements obtained at Calar-Alto observatory, in August 1998, with a 4W CW laser are presented here. This laser is used to produce a sodium-layer laser guide star for the MPE adaptive optics system (ALFA). The measurements have been done from the neighbouring 2.2m telescope with a low noise CCD camera. The first experiments and results, obtained on the Na plume and on the Rayleigh cone, are described here, as well as the theoretical light pollution estimates due to Rayleigh scattering.

1 Introduction

Adaptive Optics (AO) techniques are used for an increasing number of research programs in ground based astronomy. All modern observatories are using or are planning to use AO with Laser Guide Star (LGS) to increase sky coverage in a close future.

The LGS system generates a stray light source. Rayleigh scattering in the lower atmosphere (0 to 20 km) makes the laser beam detectable by naked eye from a distance of some hundreds of meters, depending on the laser power. If the line of sight of another telescope in the same observatory gets near the path of the laser beam during the observation, the exposure could be badly perturbed. When a *collision*, crossing of the line of sight with the laser beam, is going to occur, one has to shut-off the laser or to interrupt the observation. Wizinowich et al. (1998) estimate that a collision is succeptible to occur on 20 to 50% of the observing nights in a typical observatory like Mauna Kea. Moreover, multiple scattering can also perturb long time exposures for telescopes up to a large angular distance from the laser beam.

In order to optimise the use of observation time, it is important to evaluate exactly at which point the observation has to be interrupted: the optimal point is when the (multiple) scattered laser light level becomes equal to the sky background for the second telescope. In this perspective, not only the single and multiple Rayleigh scattering by atmospheric molecules but also Mie scattering by aerosols has to be taken into account. Modeling of these phenomena needs an experimental calibration in realistic circumstances.

Therefore in the framework of the network, 'Laser Guide Star (LGS) for 8m class telescopes', a program of Training and Mobility of Researcher from the European Commission, ESO, MPE and NUI, Galway are collaborating on studying the light pollution due to the MPE ALFA laser. This is part of a full study of the LGS operational issues.

The light pollution of the observatory is due to Rayleigh and Mie scattering of the laser beam in the low atmosphere. With the increase of LGS Adaptive Optics (AO) systems, there is a need for a laser management policy which decides when to stop the LGS use as the line of sight of one telescope gets near the laser beam. Precise measurements of single and multiple light scattering in the surroundings of the beam at various altitudes are therefore needed.

Section 2 explains the experimental set-up. Results are presented in section 3 and compared to theoretical expectations in section 4.

2 Experimental Setup



Fig. 1. Experimental set-up at Calar Alto observatory

The present experiments were carried out at the Calar-Alto observatory. The ALFA laser was launched from the 3.5m telescope pointed permanently at zenith and focussed on the sodium (Na) layer (Fig. 1). The observations were done from the 2.2m telescope situated 343 m away on a nearly pure North-South axis.

A 2048×2048 pixels SITE#1d CCD was installed at the Cassegrain focus of the 2.2m telescope. The camera, with a field of view (FOV) of $9.9' \times 9.9'$, was used for direct imaging purpose of the beam. A narrow band interference Na filter (λ_0 = 589.6nm from Elliott Scientific), with 10nm bandwidth and 50% peak transmission was used. The telescope, focussed on the laser plume, was pointed 'manually' along the laser beam at various elevations, i.e. altitudes, from 100km down to few hundred meters.